Print



AT175A1008/U

75VA, foot mounted 120/208/240 Vac transformer

Overview

Honeywell 75 VA general purpose transformers power 24 Vac circuits.

Features

- Color-coded lead wires for primary connections and screw terminals for secondary connections
- Includes fixed 1/4 inch (6mm) male quick-connects (AT175A models only) or color-coded lead wires for primary and secondary connections
- Meets Underwriters Laboratories Standard UL 1585
- Identified Class 2 not wet, Class 3 wett

Product Specifications

Dimensions (in.)	3 3/16 in. high x 2 3/8 in. wide x 3 5/8 deep
Dimensions (mm)	81 mm high x 60 mm wide x 92 mm deep
Temperature Range (F)	-20 F to +105 F
Temperature Range (C)	-29 C to +41 C
Includes	Metal end bells
Item Type	Product
Mounting	Foot mounted, plate mounted on 2x4 in. or 4x4 in. outlet box , clamp mounted using outlet box knockout, or panel mounted
Electrical Ratings	Primary voltage--120 Vac, 208 Vac, 240 Vac; Secondary voltage--27.5 V.O.C.
Frequency	60 Hz
Approvals, Underwriters Laboratories Inc.	UL Listed: A,C,F models. File # E14881
Approvals, CSA	CSA Certified: A & B models.
Electrical Connections (Primary)(in.)	9 in. leadwires
Electrical Connections (Primary)(mm)	229 mm leadwires
Electrical Connections (Secondary)(in.)	(2) screw terminals
Electrical Connections (Secondary)(mm)	(2) screw terminals
Electrical Ratings, Output	24 Vac at 75 VA