

Supply Air Damper 3-Wire Power Open/Power Close

- DEPENDABLE POWER OPEN/POWER CLOSE
- LED INDICATORS FOR FULL OPEN AND CLOSED POSITIONS
- INSULATION PAD UNDER MOTOR
- AVAILABLE SIZES: 6", 7", 8", 9", 10", 12", 14", 16" & 18"
- LONG-LIFE ACTUATOR
- 5 YEAR FACTORY WARRANTY



GENERAL DESCRIPTION

The SmartZone™ POC-series low pressure two-position damper was developed for precise control of supply air in the HVAC duct system. The solid PVC shaft eliminates external condensation and damage to the actuator drive hub. The damper actuator with built-in LED lights is designed for years of care-free operation. The power open/power close design guarantees precise control of supply air into each zone. Poron® rubber blade edges provides a positive seal for the blade. **Our gasketed damper blade is designed to compensate when installation conditions are not exact and the damper is not perfectly round.** Long-life nylon bushings insure a quiet, low friction operation of the damper. Heavy-duty galvanized steel cylinder provides strength to keep the damper round. One crimped end and one straight end allows for flexible installation. 30-Second operation to full open or closed position. A minimum open position can be set to bleed air for ventilation or duct balancing.

- QUALITY DESIGN
- SUPERIOR FEATURES
- FLEXIBLE INSTALLATION



SPECIFICATIONS

Power	24VAC, 2 VA typical (3 VA Max)
Actuator	XCI POCM Brushless Motor Design 10 in-lb Torque Power-Open/Power-Close 30 Second Operation Cycle Max 90 Degree Travel
Indicator	LED Indicates Full Open or Close
Wiring	3 Screw Terminals PO, PC, Common Use 18/3 Solid Core Wire

Part Number	D <i>Cylinder Diameter (Inches)</i>	L <i>Cylinder Length (Inches)</i>
POC06	6	12
POC07	7	12
POC08	8	12
POC09	9	12
POC10	10	12
POC12	12	12
POC14	14	14
POC16	16	16
POC18	18	18

